

INTRODUCTION

Thank you for choosing **ARC Audio's Foose Design** hi-performance mobile audio products. We hope you enjoy your experience with all our products and we welcome any questions or comments you may have.

DIRECT REPLACEMENT

ARC Audio speakers are designed to fit most applications in the original stock location without modification. Some vehicles may require minor removal of material and relocation of mounting holes to achieve a proper fit.

A WORD ON DISTORTION

Most speaker damage occurs as a result of amplifier distortion also known as "Clipping". Clipping occurs when an amp is driven beyond its maximum rated output. This kind of distortion can be hard to hear unless you know what to listen for. Any time you hear a harsh ear piercing sound at high volume your amp is probably clipping.

FD Series

FD4025	FD5025
FD6025	FD4625
FD6935	FD5725

Installation Manual

Specifications

FD6025		FD5025	
Diameter	6 ½"	Diameter	5 ¼"
Musical Power	175 watts	Musical Power	140 watts
Nor. Power	90 watts	Nor. Power	75 watts
Sensitivity	86db	Sensitivity	86db
Frequency	60hz-	Frequency	80hz-
response	20Khz	response	20Khz
IMP.	4 Ohm	IMP.	4 Ohm

FD4025

4"

Diameter **Musical Power** Nor. Power Sensitivity Frequency response IMP.

Diameter 100 watts Musical Power 55 watts Nor. Power 86db Sensitivity 110hz-Frequency 20Khz response IMP. 4 Ohm

FD6935

FD5725

FD4625

4" X 6"

100 watts

55 watts

86db

90hz-

20Khz

4 Ohm

Diameter	6" X 9"	Diameter	5" X 7"
Musical Power	185 watts	Musical Power	140 watts
Nor. Power	100 watts	Nor. Power	75 watts
Sensitivity	86db	Sensitivity	86db
Frequency	50hz-	Frequency	65hz-
response	20Khz	response	20Khz
IMP.	4 Ohm	IMP.	4 Ohm

2


CAUTION:

Please check the suitability of the installation location before you begin. Do not cut any of the car's structure. Pay attention to the mechanism of the window and door.

If you do not have experience with automotive electrical and mechanical systems contact a professional installer. Paying a qualified installer is almost always cheaper then paying a dealership to repair your car.

THE INSTALL

ARC Audio's Foose Design coaxial speakers are designed to fit most vehicles without modification. Some locations will require cutting to obtain a proper fit.



- 1. Remove the interior panel to expose the stock speaker. It may take some time to find and remove all the clip and screws to remove this panel.
- 2. Remove the stock speaker and disconnect it from the wiring.
- 3. Check the fit with the new speaker. Make sure that all the door and window hardware will clear the larger magnet.
- 4. You may have to trim some material from around or behind to speaker.
- 5. Connect the stock speaker wires to the new speaker. Tip: Use a 9V battery and quickly touch it to the terminals of the stock speaker. If the cone moves out the + of the battery is on the + of the speaker. If you noted the color of wire connected to this terminal then you now the + speaker wire.
- 6. Install the speaker in the location. You may have to drill new holes to secure the speaker.
- 7. Reinstall the panel. Congratulations you finished and ready to enjoy your new system.

If you have any Question about this product please call ARC Audio Technical Service:

209-543-8706

ARC AUDIO WARRANTY AND SERVICE GUIDELINES

ARC AUDIO warrants all new speakers and subwoofers against defects in material and workmanship for a period of **NINTEY (90) DAYS** from the original date of purchase on all over the counter purchases not installed by an **AUTHORIZED ARC AUDIO RETAILER**. On all FD (Foose Designs) models, the limited warranty is **EXTENDED NINE (9) MONTHS** additional from the original purchase date if the product is originally installed by an **AUTHORIZED ARC AUDIO RETAILER** and is accompanied by a valid copy of the original receipt showing a charge for the installation. This warranty is not transferable and applies only to the **original retail purchaser** of the product from an authorized ARC AUDIO retailer. Upon inspection by ARC AUDIO will, at its sole discretion, repair or replace the defective product with new or similar conditioned product at no charge.

THIS WARRANTY DOES NOT COVER INSTALLATION OR DAMAGE RESULTING FROM ACCIDNT, MISUSE, ABUSE, IMPROPER WIRING, OPERATION OUTSIDE OF UNIT OUTSIDE OF MANUFACTURES SPECIFICATIONS, OR AGAINST INSTRUCTIONS IN OWNERS MANUAL. IN ADDITION ANY PRODUCT THAT HAS BEN OPENED, TEMPERED WITH OR MODIFIED, OR IF ANY SERIAL NUMBERS HAVE BEEN REMOVED WILL NOT BE COVERED BY ANY PART OF THE MANUFACTURES WARRANTY.

All warranty returns should be sent to ARC AUDIO freight prepaid and must be accompanied by proof of purchase (a copy of the original sales receipt). Direct returns from consumers or non-authorized retailers will be refused unless specifically authorized by ARC AUDIO with a valid return authorization number.

All warranty returns must be packed in original packaging and be accompanied by a copy of the original sales receipt. Product damaged in shipment due to improper packaging will not be covered underthis warranty and the customer or retailer will be charged full cost to repair the specific piece of product back to a like new or similar condition.

In no event will ARC AUDIO be liable for incidental, consequential, or other damages resulting from the use of this product, this includes but is not limited to, damage of hearing, property or person, damage based upon inconvenience or on loss of use of the product, and to the extent permitted by law, damages for personal injury. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. This warranty applies to products sold and used in the United States of America. In all other countries please contact your distributor

For warranty and non-warranty repairs, send to: ARC Audio 4719 Green Leaf Cr. #4 Modesto CA, 95356

